

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035375 A1

(51) International Patent Classification⁷: B63B 21/50,
E21B 17/01, 43/013

(74) Agents: VAN WESTENBRUGGE, Andries et al.; Ned-
erlandsch Octrooibureau, Scheveningseweg 82, P.O. Box
29720, NL-2502 LS The Hague (NL).

(21) International Application Number:
PCT/NL2003/000695

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 15 October 2003 (15.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02079288.3 16 October 2002 (16.10.2002) EP

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): SINGLE
BUOY MOORINGS INC. [CH/CH]; 5, route de Fribourg,
CH-1723 Marly (CH).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): POLLACK, Jack
[US/US]; 14855 Memorial Drive 2112, Houston, TX
77079 (US); POLDERVAART, Leendert [NL/FR]; 92,
Les Hautes de Monte-Carlo, F-06320 La Turbie (FR).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: RISER INSTALLATION VESSEL AND METHOD OF USING THE SAME



(57) Abstract: The invention relates to a vessel (1) for exploration of hydrocarbons. The vessel comprises one or more risers (13, 14) extending from the vessel to the seabed, a hydrocarbon processing unit (5) connected to the one or more risers and to a storage or transport structure (6) for storing the processed hydrocarbons. The vessel is anchored to the seabed, the vessel comprising a lifting means (22) for lowering risers vertically towards the sea bed and for connecting a riser with a first end to a subsea hydrocarbon structure (7), which riser comprises a connector (18) on a second end, the vessel comprising a connector (16) for attaching to the riser connector and for placing the riser in fluid connection with the processing unit.

WO 2004/035375 A1

Riser installation vessel and method of using the same

The invention relates to a vessel for the exploration of hydrocarbons, comprising
5 one or more risers extending from the vessel to the seabed, a hydrocarbon processing
unit connected to the one or more risers and a storage or transport structure for the
processed hydrocarbons. The invention also relates to a method of installing one or
more steel riser pipes.

From Offshore Technology Conference OTC 11875, Houston, Texas, 1-4 May
10 2000 with the title "Hybrid Riser for Deepwater Offshore Africa", Loïc des Déserts -
Doris Engineering, a riser pipe for deep waters is described comprising a steel outer
casing with a number of production risers, gas and water injection lines and insulation
made of foam which also confers buoyancy to the riser pipe. The riser pipe is
assembled on shore and towed to location where it is uprighted and connected to the
15 foundation on the seabed. The upper part of the riser is connected to a submerged buoy.
After installation of the hybrid riser pipe, the submerged buoy is connected via flexible
jumpers to the surface facility such as an FPSO which may be located at a distance
between 70-200 m from the buoy.

The known method has as a disadvantage that during riser installation no
20 hydrocarbon production and/or processing can take place. Furthermore, installation
requires special and dedicated installation equipment. Specialised installation vessels
are designed to work in as large as possible sea states and are hence, sizeable and costly
equipment.

From US-4,182,584 it is known to attach a free-standing marine production riser
25 for use in deepwater between a base portion and a submerged buoy. With a derrick-
equipped vessel, such as a semi-sub, the riser casing is lowered through the central part
of the buoy and coupled to the bottom until the rigid riser part is completed. Next, a
flexible hose is attached to a surface facility for hydrocarbon production and
processing.

30 Again, the use of separate vessels for riser installation and for hydrocarbon
production / processing requires scheduling and mobilising the installation vessel to site
at large day rates and the demobilisation of the installation vessel after installation of
the riser.

Furthermore, in view of the large costs of the installation vessel, as many risers as possible would be installed when the installation vessel is on site, which implies capital outlay, fatigue and maintenance of the risers which are not producing.

It is hence an object of the present invention to provide a flexible system for riser
5 installation and hydrocarbon production and/or processing, avoiding complex scheduling of the installation vessel and allowing riser installation at a suitable moment.

It is a further object of the present invention to provide a flexible riser installation method using relatively simple installation equipment.

10 It is another object of the present invention to provide a riser installation method in which during hydrocarbon production and/or processing additional risers can be rapidly installed.

Hereto, the vessel according to the present invention is characterised in that the vessel is anchored to the seabed, the vessel comprising a lifting means for lowering risers
15 vertically towards the sea bed and for connecting a riser with a first end to a subsea hydrocarbon structure, which riser comprises a connector on a second end, the vessel comprising a connector for attaching to the riser connector and for placing the riser in fluid connection with the processing unit.

With the vessel of the present invention, no dedicated expensive riser installation
20 vessels need to be used. By installing the risers from the vessel, it is possible to start hydrocarbon production and processing while at the same time installing the risers during stable weather conditions. The vessel of the present invention allows hydrocarbon production while obtaining information from the hydrocarbon field. When after start of hydrocarbon production it is required to drill and connect other nearby
25 wells, this can be carried out simply from the installation equipment on the vessel.

The processed hydrocarbons may be stored in tanks on the vessel and transported to shore via shuttle tankers or may be transported via a pipeline from the vessel to another vessel or to an on-shore installation.

The means for lowering the risers may comprise a lifting device of the type such
30 as described in European patent application number 02075311.7 which was filed on 25 January 2002 in the name of the applicant. The lowering equipment described herein is relatively simple and takes up little deck space leaving sufficient room for hydrocarbon production and/or processing equipment.

In a preferred embodiment, the risers are extending alongside of the vessel. The vessel may comprise a derrick and a drill string extending to the seabed, such as through a moon pool in the vessel.

5 The risers may comprise a lower rigid (steel) part and may be connected to a submerged buoy, the upper part of the risers being made of a flexible material and extending from the buoy to the vessel. The vessel may be spread moored whereas the risers may be installed through a central shaft in the vessel according to another embodiment.

10 Some embodiments of a method according to the present invention will be described in detail with reference to the accompanying drawings. In the drawings:

Fig. 1 shows a schematic view of a hydrocarbon production and/or processing vessel for carrying out the method of the present invention;

Figs. 2-4 show the sequence of horizontal extension of a riser, hook-up of the riser to a sub sea wellhead and connection to the vessel;

15 Figs. 5-8 show another method of riser installations according to the present invention;

Fig. 9 shows an alternative method of riser installations according to the present invention employing a work vessel;

20 Fig. 10 shows an embodiment of a vessel and a lifting device for carrying out the method of the present invention;

Figs 11-13 show a detailed view of the lifting device of Fig. 10;

Figs. 14-15 show a riser configuration installed by the method of the present invention;

25 Figs. 16-17 show a vessel having a turret moored configuration carrying risers that have been installed according to the present invention;

Fig. 18 shows a spread-moored anchoring configuration of a vessel carrying risers according to the present invention;

Figs. 19-22 show a schematic view of a further embodiment of a method according to the invention;

30 Fig. 23 shows an embodiment of the method using a separate working vessel;

Figs. 24-30 show a riser installation method using a separate work vessel; and

Fig. 30 shows a method of obtaining a J-configuration of the riser using a work vessel.

Fig. 1 shows a hydrocarbon production and/or processing vessel 1 according to the present invention. The vessel 1 may be connected to the seabed 2 via a number of anchor lines 3 which may be connected to a chain table 4 provided at the bottom of the vessel 1. Alternatively, other configurations, such as a turret moored or a spread moored configuration, are also possible.

The vessel 1 comprises a hydrocarbon-processing unit 5, such as oil and water separation systems, gas liquefaction equipment, a regassification plant, etc. Storage tanks 6 in the vessel 1 may contain crude and/or processed hydrocarbons.

From wellheads 7, 8 on the seabed 2, lower riser parts 9, 10 extend to submerged buoys 11, 12. From the buoys 11, 12 flexible risers 13, 14 extend to connectors 15, 16 on the vessel 1. Each riser 13, 14 comprises at its upper end a connector 17, 18 which attaches to connectors 15, 16 to place risers 13, 14 in fluid connection with the processing unit 5 and/or hydrocarbon storage tanks 6, via ducts 19, 20.

On deck of the vessel 1, a lifting means 22 is provided having an upper lifting arm 23 and lower lifting arm 24 which can be moved in a vertical direction towards and away from each other. In case the vessel 1 is a FPDSO, on deck of the vessel 1, a derrick 25 may be placed for drilling of a new well 28, a drill string 29 extending through a shaft 30 in the vessel 1.

Figure 2 shows the steel catenary riser (SCR) 9 being with its upper end connected to the lifting means 22 and extending at an angle α of 2° - 10° with the vertical. The work vessel 38 pulls out the riser 9 via a winch 40 and chain or cable 41 connected to the lower end of the riser 9, over the sea bed, to the well head 7 or to a well head connection, such as a manifold and the like. Instead of a work vessel 38 for pulling the riser 9, it may be pulled to the well head 7 by a moored vessel using a winch. The chain or cable 41 preferably has a similar linear weight (kg/m) as the riser 9 in water, such that the riser 9 and chain or cable 41 follow the same catenary curve hence avoiding moments exerted on the pipe and consequent damage to the riser 9. This is especially relevant for deep waters, such as water depths of 500 m and deeper, for instance between 1000 and 2000 m.

As shown in Fig. 3, the upper end of the riser 9 is connected to the lifting means 22 via a chain or cable 34 at the moment when the lower end of the riser 9 is situated near the well head 7, while the work vessel 38 continues to drag the riser 9 over the sea bed towards the well head 7. When the lower riser end has reached the well head 7, the

riser is lowered from the work vessel 38 and is connected to the well head via a remotely operated vehicle (ROV), not shown in the drawing. The chain or cable 41 is disconnected from the riser by the ROV.

Next, as is shown in Fig. 4, the chain or cable 34 is pulled upward, so that the riser will have an inclination of about 15° - 20° with respect to the vertical. With this angle of inclination, the riser 9 is connected to the vessel for transport of hydrocarbons from the well head 7 to the vessel.

Figs. 5-8 show the process of installing a rigid riser part 32 having a connector 31 at its lower end to stab onto a wellhead 30 on the seabed 2. The riser 32 is assembled from segments 33, which may be stored on the vessel 1. The riser 32 is lowered via the lifting device 22 by releasing a clamping mechanism of the lower arm 24 and lowering upper arm 23. Next, the clamping mechanism on the lower arm 24 is engaged with the top part of the risers 32, the clamping mechanism on the upper arm 23 is released and the upper arm 23 returns to its upward position. Another segment 33 is clamped in the upper arm 23 and is connected to the riser section depending from lower arm 24 and the lowering cycle is repeated. A riser supporting buoy 11 may be stored on the vessel and is attached to the top of riser 32, as is shown in Fig. 3. At the position of the lifting device 22, the upper part of the buoy 11 may be connected to the upper arm 23. As shown in Fig. 4, the buoy 11 is lowered from a cable 34 whereas a remotely operated vehicle 35 is operated from the vessel to attach connector 31 to the wellhead 30. After attaching the connector 31 buoyancy is added to buoy 11 and the remotely operated vehicle 35 is operated to attach a flexible riser 36 with its lower end to the buoy 11 to be in fluid connection with riser 32 and with connector 37 at its upper end to connector 16 on the vessel 1 to be in fluid communication with processing unit 5.

In the embodiment as shown in Fig. 9, a smaller vessel or tugboat 38 assists in lowering the lower end 39 of flexible riser 36 via a winch 40.

Fig. 10 shows the vessel 1 comprising the lifting device 22 according to the present invention. The lifting device 22 comprises a vertical frame 23' carrying the cable 34 having at spaced-apart locations support members in the form of broadened parts 45, 46, 47. At the end of the cable 34, a connector 44 is provided that is attached to the buoy 11, which is being lowered via the cable 34. The cable 34 is stored in a looped configuration in a storage compartment or hawse-hole 40, substantially without being tensioned. From the storage compartment 40, the cable 34 is guided via a sheave

52 to an upper lifting structure 53 and a lower lifting structure 54. The upper lifting structure can travel up and down along the vertical frame 23' and can releasably engage with the broadened parts 45, 46, 47 on the cable 34. Stationary lower lifting structure 54 can also engage and be disengaged with the broadened parts 45, 46, 47. By the
5 lower releasing lifting structure 54 and lowering the cable suspended from upper lifting structure 53, the buoy 11 is lowered. After lowering of the upper lifting structure 53 by a certain amount, the lower lifting structure 54 is engaged with one of the broadened parts of the cable 34, whereas the upper lifting structure 53 disengages from the cable and is returned to its upper position. In this way, the buoy 11 can be successively
10 lowered until it reaches its desired depth. The buoy 11 may, prior to being lowered from lifting device 22, be placed overboard by a crane 57, which is thereafter disengaged such that the buoy can be lowered from cable 34.

As an alternative to the looped configuration, the cable 34 may also be stored in the compartment 50 in a coiled from, for instance around a conical raised bottom part
15 of compartment 50, or be stored on a drum or, again, alternatively as separate line sections.

Fig. 11 shows a detailed view of upper and lower lifting structures 53, 54. The upper lifting structure 53 comprises two parallel cylinders 60, 60', which are powered by hydraulic pump 62. Each cylinder comprises a sleeve 63, 63' and a rod 64, 64'
20 moveably received within the sleeve 63, 63'. At the end of each rod 64, 64' a pulley 65, 65' is connected. Both pulleys are interconnected via a frame 66. A moveable clamp 67, 67' is slidably connected along each rod 64, 64' and along each sleeve 63, 63'. The clamps 67, 67' are connected to the end part of a cable having a first cable section 68, 68' extending from the pulley 65, 65' to the respective clamp 67, 67' and a second cable
25 section 69, 69' extending along the rod 64, 64' and sleeve 63, 63' to a fixed position 71, 71'. As shown in Fig. 11, the lower lifting structure 54 is clampingly engaged via clamps 55, 55' with a part of the cable 34. An upper cable section 72 is engaged with clamps 67, 67' of upper lifting structure 53, such as shown in Fig. 12. Thereafter, the clamps 55, 55' of the lower lifting structure 34 are opened, while upper clamps 67, 67'
30 remain engaged with the broadened part on the upper cable section 72. Under control of the hydraulic pump 62, the rods 64, 64' are under the weight of the cable 34 and buoy 11 and riser 32, pulled into sleeves 63, 63' such that the clamps 67, 67' descend along the sleeves 63, 63'. In the lowered position, such as shown in Fig. 13, the clamps 55, 55'

engage with a broadened part of cable section 34. Hereby, the whole cable weight and the weight of the buoy 11 and riser 32 are again supported from the lower lifting structure 54. The clamps 67, 67' are then disengaged and the pulleys 65, 65' are returned to their upper position as shown in Fig. 11. In an advantageous embodiment, the lifting structures 53, 54 are formed as an integral unit in a frame, which is suspended from the crane 57. In this way, heavy loads can be handled at large water depths from vessels having a standard crane by the lifting device of the present invention.

Instead of a lifting means as shown in Figs. 11-13, a heave-compensated winch could be used.

Fig. 14 shows a riser configuration installed according to the present invention in which a connector base 80 is attached to vertical riser 32, which connector base 80 is connected to a wellhead 81 via a horizontal bottom pipe 82. In the embodiment of Fig. 15, the riser 32 is connected via a J-curved section 84 to the wellhead 81 and is being tensioned to the seabed via tensioning base 83. Alternatively, the riser 10 may be connected to a connector base 85 in a J-curved manner, similar to riser 32. After completion of the drilling operation, the drilling riser 29 and the derrick 25 may be removed.

Fig. 16 shows a turret moored vessel 90 in which anchor lines 91, 92 are with one end attached to a turret 98 and with another end to the seabed. Risers 93, 94 are connected to a hydrocarbon processing unit on the vessel. Through a lifting means 96, riser sections 97 are lowered from the deck of the vessel 90 through a central shaft 95 in the turret 98 to be attached to a subsea wellhead.

In the embodiment shown in Fig. 17, a turret-moored barge is shown in which the lifting device 96 is placed at the side of the vessel. Via a small tug 97, the riser installation may be assisted.

Fig. 18 shows a spread-moored configuration in which the risers 93, 93', 94, 94' are placed at the regularly spaced positions on the sides of the vessel, and are after lowering from crane 96 and attached to a buoy, towed in position by a mall tugboat.

Figs 19-22 show a method of riser installation in which first a connector base 80 is lowered onto the seabed. Via ROV 35 a first end of riser 82 is connected to wellhead 81 whereafter the vessel 1 is moved towards connector base 80 for connection of the other end of riser 82, such that bottom pipe 82 extends substantially horizontally on the

seabed 2. In the next steps, a vertical riser part, a buoyancy member and flexible riser such as shown in Fig. 14 may be installed.

In the embodiment of Fig. 23, riser sections 83 and buoyancy member 84 are supplied from a separate supply vessel 38.

5 In the embodiment of Figs. 24-30, the small working vessel 38 is employed to lower the riser 32 and buoy 11 and to operate ROV 35 for connection of the risers 32 to a wellhead and for installing flexible riser 13.

10 Finally, in the embodiment of Fig. 31 the working vessel 38 places the horizontal riser section 84 on the seabed in an upwardly extending J-configuration to obtain the riser configuration as shown at the left-hand side of Fig. 15.

CLAIMS

1. Vessel for exploration of hydrocarbons, comprising one or more risers extending from the vessel to the sea bed, a hydrocarbon processing unit connected to the one or
5 more risers and to a storage or transport structure for storing or transporting of the processed hydrocarbons, characterized in that, the vessel is anchored to the seabed, the vessel comprising a lifting means for lowering risers vertically towards the sea bed and for connecting a riser with a first end to a subsea hydrocarbon structure, which riser comprises a connector on a second end, the vessel comprising a connector for attaching
10 to the riser connector and for placing the riser in fluid connection with the processing unit.
2. Vessel according to claim 1, the storage structure comprising a tank on the vessel.
- 15 3. Vessel according to claim 1 or 2, wherein the means for lowering comprise a crane, placed on the vessel.
4. Vessel according to claim 1, 2 or 3, the risers extending alongside of the vessel.
- 20 5. Vessel according to claim 1, 2, 3 or 4, wherein the vessel comprises a derrick and a drill string extending from the derrick to the seabed.
6. Vessel according to claim 5, wherein the drill string extends through a shaft in the vessel.
- 25 7. Vessel according to any of the preceding claims, the riser comprising a lower part being made of a rigid material and being connected to a submerged buoy, an upper part of the riser being made of a flexible material and extending from the buoy to the vessel.
- 30 8. Vessel according to any of the preceding claims, the vessel comprising a shaft extending from deck level to keel level, the lifting means being located near the shaft for lowering a riser through the shaft towards the sea bed.

9. Method of installing a number of risers between a floating vessel and the sea bed, the vessel comprising a hydrocarbon processing unit connected to the one or more risers and a storage or transport structure for storing or transporting of the processed hydrocarbons, the vessel being anchored to the sea bed, characterized in that, the vessel
- 5 comprises a lifting means for lowering risers vertically towards the sea bed and for connecting a riser with a first end to a subsea hydrocarbon structure, and a connector means on a second end of the riser and on the vessel for placing the riser in fluid connection with the processing unit, the method comprising the steps of
- lowering the first riser part from the lifting means,
 - 10 - connecting an upper end of the riser to a buoyancy device,
 - lowering the riser and buoyancy device,
 - connecting the lower end of the first riser part to a subsea structure with a remote operated vehicle,
 - releasing the buoyancy device from the lifting means,
 - 15 - lowering the flexible riser part from the lifting device
 - connecting the lower part of the flexible riser part to the buoyancy device, in fluid communication with the lower riser part, and the upper end of the flexible riser part to the processing unit.
- 20 10. Method according to claim 9, wherein prior to lowering the first riser part,
- a connector base is lowered to the seabed at a distance from a distribution member,
 - a transverse pipe section is lowered to the distribution member , and is attached thereto,
 - 25 - the vessel is moved sideways to extend the transverse pipe section over the seabed from the distribution member to the connector base,
 - the transverse pipe section is connected to the connector base.
11. Method according to claim 8 or 9, wherein the lower end of the flexible riser part
- 30 is lowered from a second vessel alongside the vessel.
12. Method according to claim 8 or 9, wherein the lower riser part and the buoyancy device are lowered from a second vessel alongside the vessel.


13. Method according to claim 11, wherein the lower riser part is attached to the connector base and the second vessel is displaced sideways to extend the lower riser part at least partially horizontally over the seabed.

ABSTRACT




The invention relates to a vessel for exploration of hydrocarbons. The vessel comprises one or more risers extending from the vessel to the seabed, a hydrocarbon processing unit connected to the one or more risers and to a storage or transport structure for storing the processed hydrocarbons. The vessel is anchored to the seabed, the vessel comprising a lifting means for lowering risers vertically towards the sea bed and for connecting a riser with a first end to a subsea hydrocarbon structure, which riser comprises a connector on a second end, the vessel comprising a connector for attaching to the riser connector and for placing the riser in fluid connection with the processing unit.

da
to
d


to
d



2/18

Fig 2**Fig 3****Fig 4**

3/18









Fig 9




6/18

Fig 10



7/18










Fig 16

Fig 17



10/18

Fig 18

11/18

Fig 20





Fig 19



12/18





Fig 23




Fig 25






Fig 24



16/18

Fig 29




Fig 28






Fig 30

Fig 31

INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 03/00695

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 B63B21/50 E21B17/01 E21B43/013		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 B63B E21B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 347 912 B1 (THOMAS PIERRE-ARMAND) 19 February 2002 (2002-02-19) column 3, line 3 - line 24; figures column 5, line 39 - column 6, line 25 ---	1
A	US 6 085 851 A (HERRMANN ROBERT P ET AL) 11 July 2000 (2000-07-11) column 5, line 10 - line 26; figures ---	1
A	US 4 643 614 A (LAURSEN NILS K) 17 February 1987 (1987-02-17) abstract; figures ---	1,9
A	US 4 074 541 A (LOCHRIDGE JOE COOPER) 21 February 1978 (1978-02-21) abstract; figures ---	1,9
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed </div> <div style="width: 45%;"> "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family </div> </div>		
Date of the actual completion of the international search <div style="text-align: center; font-weight: bold;">28 January 2004</div>	Date of mailing of the international search report <div style="text-align: center; font-weight: bold;">04/02/2004</div>	
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl Fax: (+31-70) 340-3016	Authorized officer <div style="text-align: center; font-weight: bold;">Weland, T</div>	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 03/00695

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 182 584 A (HETTINGER FREDRIC L ET AL) 8 January 1980. (1980-01-08) cited in the application abstract; figures ---	1,9
A	DÉSERT: "Hybrid riser for deepwater offshore Africa" OFFSHORE TECHNOLOGY CONFERENCE, vol. etc, no. 11875, 1 - 4 May 2000, pages 1-9, XP002234782 houston, texas cited in the application the whole document -----	1,9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/NL 03/00695

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 6347912	B1	19-02-2002	FR	2782341 A1	18-02-2000
			AU	754800 B2	28-11-2002
			AU	4347799 A	02-03-2000
			BR	9904472 A	29-08-2000
			EA	1520 B1	23-04-2001
			EP	0979923 A1	16-02-2000
			NO	993852 A	14-02-2000
			US	2002048492 A1	25-04-2002
US 6085851	A	11-07-2000	AU	710636 B2	23-09-1999
			AU	1827897 A	26-11-1997
			BR	9706592 A	28-12-1999
			CA	2225755 A1	13-11-1997
			CN	1194679 A ,B	30-09-1998
			DE	69718592 D1	27-02-2003
			DK	836668 T3	12-05-2003
			EP	1148206 A2	24-10-2001
			EP	1277913 A2	22-01-2003
			EP	0836668 A1	22-04-1998
			ES	2191820 T3	16-09-2003
			JP	3002545 B2	24-01-2000
			JP	10508270 T	18-08-1998
			NO	976037 A	02-03-1998
			NO	20020181 A	02-03-1998
			NZ	329650 A	29-09-1999
			US	6047781 A	11-04-2000
			WO	9742393 A1	13-11-1997
			US	6056071 A	02-05-2000
			US	6068069 A	30-05-2000
US 4643614	A	17-02-1987	NL	8402545 A	01-08-1985
			ES	8700635 A1	16-01-1987
			GB	2163404 A ,B	26-02-1986
			NO	853265 A ,B,	21-02-1986
US 4074541	A	21-02-1978	GB	1599198 A	30-09-1981
			NO	782240 A	08-01-1979
US 4182584	A	08-01-1980	AU	522683 B2	17-06-1982
			AU	4873779 A	17-01-1980
			CA	1111345 A1	27-10-1981
			ES	482326 A1	16-08-1980
			FR	2439290 A1	16-05-1980
			GB	2024766 A ,B	16-01-1980
			JP	1376176 C	22-04-1987
			JP	55016196 A	04-02-1980
			JP	61046637 B	15-10-1986
			NO	792277 A ,B,	11-01-1980